

## AV-35 Bronze Globe Steam Stop Valve No.5, Screwed Ends, PN-20

## **Features**

Testing Standard BS EN 12266-Part 1

Pressure / Class Rating PN-20

Body Material Cum Standard Bronze (BS EN 1982 Gr. CC491K)

Product Description Screwed in Bonnet, Inside Screw, Rising Stem with

Backseat Arrangement, Handwheel Operated

Type of Seat Renewable Seat
Type of Disc Renewable Disc
Trim 13% Cr. (SS 410)

End Details Screwed Female BSP Parallel Threads (BS-21)
Test Pressure Body: 450 Psig (Hyd.), Seat & Back Seat: 320 Psig

(Hyd.)

Max. Working Pressure 150 Psig (Steam)

Notes


Other screwed end specifications can be provided on request.

Suitability

Water, Steam, Oil



| S.No | Description | No. | Material           |
|------|-------------|-----|--------------------|
| 1    | Body        | 1   | Bronze             |
| 2    | Seat Ring   | 1   | Stainless Steel    |
| 3    | Disc        | 1   | Stainless Steel    |
| 4    | Disc Nut    | 1   | Bronze             |
| 5    | Bonnet      | 1   | Bronze             |
| 6    | Gland Nut   | 1   | Bronze             |
| 7    | Gland       | 1   | Bronze             |
| 8    | Stem        | 1   | Stainless Steel    |
| 9    | Handwheel   | 1   | Cast Iron          |
| 10   | Packing     | -   | Graphited Asbestos |



## **Dimensional Data**

| Size (mm) | FF  | Т      | Н   | ØHW |
|-----------|-----|--------|-----|-----|
| 8         | 50  | 1/4"   | 86  | 50  |
| 10        | 52  | 3/8"   | 86  | 50  |
| 15        | 56  | 1/2"   | 100 | 56  |
| 20        | 68  | 3/4"   | 115 | 71  |
| 25        | 79  | 1"     | 125 | 71  |
| 32        | 87  | 1.1/4" | 137 | 89  |
| 40        | 102 | 1.1/2" | 155 | 95  |
| 50        | 119 | 2"     | 162 | 119 |
| 65        | 136 | 2.1/2" | 185 | 127 |
| 80        | 164 | 3"     | 195 | 175 |
| 100       | 200 | 4"     | 240 | 195 |

Phone: +91 181 5001111 Fax: +91 181 2290611 Email: sales@atamfebi.com