



ATAM

Valves, Fittings & Boiler Mountings

febi[®]

Ball Valves



**WHERE
SAFETY & RELIABILITY
COMES FIRST**



**Plumbing & Firefighting
PRODUCT RANGE**



ATAM

COMPACT PRESSURE REDUCING VALVES STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"-2"

Pressure Rating : PN-16

Max. Working Pressure : Max. Inlet 16 Bar & Outlet Pressure Range 1.5-5 Bar

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

TEST & DRAIN BALL VALVES STAINLESS STEEL (CF8 / CF8M)

Size Range : 1"-2"

Pressure Rating : PN-20

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

LEVER OPERATED BALL VALVES STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/4"-4"

Pressure Rating : PN-20, PN-40, 1000PSig, 2000PSig (Hyd.)

End Details : Screwed Female BSP Parallel Threads (BS-21)

Flanges as per ASME B16.5 CL-150

CAST IRON

Size Range : 1/2"-4"

Pressure Rating : CL-125 / PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)

Flanges as per BS-10 Table-F, ASME B16.5 CL-150

BRONZE

Size Range : 1/4"-4"

Pressure Rating : PN-20

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

CHECK VALVES

BRONZE

Size Range : 1/4"-4"

Pressure Rating : PN-10, PN-16, PN-20

End Details : Screwed Female BSP Parallel Threads (BS-21)

CAST IRON

Size Range : 1.1/2"-20"

Pressure Rating : PN-10, PN-16, PN-25

End Details : Wafer Type suitable to insertion between flanges
PN-10 / PN-16 / CL-150 / Table-D

Flanges as per BS-10 PN-10 / PN-16

CAST STEEL

Size Range : 1/2"-24"

Pressure Rating : PN-40, CL-150

End Details : Flanges as per BS-10 TABLE-H, PN-40, ASME B16.5 CL-150

STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"-2"

Pressure Rating : PN-16, PN-20, PN-25 (Hyd.)

End Details : Screwed Female BSP Parallel Threads (BS-21)

ATAM

LEVER OPERATED WAFER TYPE

BUTTERFLY VALVES

CAST IRON

Size Range : 1.1/2"-24"

Body / MOC : CI / SGI / CS / ALUMINIUM

Disc MOC : SGI / CF8 / CF8M

Pressure Rating : PN-10, PN-16, PN-25

End Details : Wafer Type suitable to insertion between flanges
PN-10 / PN-16 / CL-150 / Table-D

Gear & Actuator are also provided on demand.





ATAM



ATAM

GATE VALVES



BRONZE

Size Range : 1/4"-6", Stem : Rising / Non-rising

Pressure Rating : PN-10, PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)

CAST IRON



Size Range : 2"-24"

Stem : SS 410 Rising / Non-Rising

Pressure Rating : PN-10, PN-16

End Details : Flanges as per BS-10 PN-10 / PN-16

CAST STEEL

Size Range : 2"-24"

Pressure Rating : CL-150

End Details : Flanges as per ASME B16.5 CL-150

STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"-2"

Pressure Rating : PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)

ATAM

GLOBE VALVES



BRONZE

Size Range : 1/2"-4"

Pressure Rating : PN-10, PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)

CAST STEEL

Size Range : 1/2"-12"

Pressure Rating : PN-40, CL-150

End Details : Flanges as per BS-10 Table-H, PN-40, ASME B16.5 CL-150



ATAM



ATAM

GLOBE VALVES
STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"-2"

Pressure Rating : PN-16, PN-20, PN-25

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

STRAINERS
BRONZE

Size Range : 1/2"-2.1/2"

Pressure Rating : PN-10, PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)



CAST IRON

Size Range : 1/2"-14"

Pressure Rating : PN-10, PN-16

End Details : Screwed Female BSP Parallel Threads (BS-21)

Flanges as per BS-10 Table-D, Table-H



CAST STEEL

Size Range : 1"-10"

Pressure Rating : CL-150

End Details : Flanges as per ASME B16.5 CL-150

STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"-2"

Pressure Rating : PN-20

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

PRESSURE RELIEF VALVES
BRONZE

Size Range : 1/2"-3", Type : Open Discharge / Enclosed Discharge

Pressure Rating : PN-10

End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

SIGHT GLASS FLOW INDICATOR VALVES BRONZE

Size Range : 1/2"-2", Type : Single Window / Single Window with Impeller
Pressure Rating : PN-10
End Details : Screwed Female BSP Parallel Threads (BS-21)



ATAM

FLOAT VALVES STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"- 1"
Pressure Rating : PN-10
End Details : Screwed Male BSP Parallel Threads (BS-21)



ATAM

AIR VENT VALVE STAINLESS STEEL (CF8 / CF8M)

Size : 1"
Pressure Rating : PN-10
End Details : Screwed Male BSP Parallel Threads (BS-21)



ATAM

CONCEALED BALL VALVE STAINLESS STEEL (CF8 / CF8M)

Size Range : 1/2"- 2"
Pressure Rating : PN-25
End Details : Screwed Male BSP Parallel Threads (BS-21)



ATAM



ATAM

**LANDING / FIRE HYDRANT VALVE, TYPE-A FLANGE ENDS
STAINLESS STEEL (CF8 / CF8M)**



Size : 3"

Pressure Rating : CL-125 (14 Bar)



ATAM

**FOOT VALVES
BRONZE**

Size Range : 1/2" - 8"

Pressure Rating : PN-20

End Details : Screwed Female BSP Parallel Threads (BS-21)



**BALL TYPE FOOT VALVE
CAST IRON**

Size Range : 2" - 12"

Pressure Rating : PN10 / PN16

End Details : Flanges as per BS-10 Table-D, PN-16, ASME B16.5 CL-150



ATAM

**KINETIC TYPE AIR RELEASE VALVE
CAST IRON**

Size Range : 1.1/2" - 8"

Pressure Rating : PN-10

End Details : Flange Ends as per IS: 1538 PN-10



ATAM

**RESILIENT SEATED GATE VALVE
CAST IRON**

Size Range : 2" - 16"

Pressure Rating : PN-10, PN-16

End Details : Flange Ends as per EN 1092-2, IS 14846



Valves, Fittings & Boiler Mountings



Ball Valves

Watch Corporate Video
Scan to download Catalogue



Atam Valves Limited
1051, Outside Industrial Area,
Jalandhar - 144004 Punjab. INDIA

Phone : +91 181 5001111 Fax : +91 181 2290611

Email : sales@atamfebi.com

www.atamvalves.in